

Field of invention

5

10

15

20

30

It is further possible to assign different encryption keys of the same algorithm to different data columns. With multiple keys in place, intruders are prevented from gaining full access to any database since a different key could protect each column of encrypted data.

In the above mentioned solutions the system administrator is responsible for setting the user permissions. Thus, for a commercial database, the system administrator operates through a middle-ware, the access control system (ACS), which serve for authentication, encryption and decryption. The ACS is tightly coupled to the database management system (DBMS) of the database. The ACS controls access in real-time to the protected elements of the database.

Such a security solution provides separation of the duties of a security administrator from a database administrator (DBA). The DBA's role could for example be to perform usual DBA tasks, such as extending tablespaces etc, without being able to see (decrypt) sensitive data. The SA could then administer privileges and permissions, for instance add or delete users.

For most commercial databases, the database administrator has privileges to access the database and perform most functions, such as changing password of the database users, independent of the settings by the system administrator. An administrator with root privileges could also have full access to the database. This is an opening for an attack where the DBA can steal all the protected data without any knowledge of the protection system above. The attack is in this case based on that the DBA impersonates another user by manipulating that users password, even though the user's password is enciphered by a hash algorithm. An attack could proceed as follows. First the DBA logs in as himself, then the DBA reads the hash value of the users password and stores this separately. Preferably the DBA also copies all other relevant user data. By these actions the DBA has created

006277" 50052450

a snapshot of the user before any altering. Then the DBA executes the command "ALTER USER username IDENTIFIED BY newpassword". The next step is to log in under the user name "username" with the password "newpassword" in a new session. The DBA then resets the user's password and other relevant user data with the previously stored hash value.

Thus, it is important to further separate the DBA's and the SA's privileges. For instance, if services are outsourced, the owner of the database contents may trust a vendor to administer the database. Then the role of the DBA belongs to an external person, while the important SA role is kept within the company, often at a high management level. Thus, there is a need for preventing a DBA to impersonate a user in a attempt to gain access to the contents of the database.

Object of the invention

It is therefore an object of the present invention to provide a method and a system for preventing an administrator impersonating a user of a relational database overcoming the above mentioned problems.

The object is achieved by a method and a system according to the appended claims.

Summary of the invention

According to the invention a method for preventing an administrator impersonating a user of a relational database, which database at least comprises a table with at least a user password, wherein said password is stored as a hash value, said method comprises the steps of:

adding a trigger to said table, said trigger at least triggering an action when an administrator alters said table through the database management system (DBMS) of said database;

replacing said stored password hash value with said new password hash value.

Preferably, the method comprises the further steps
of:

25 With the method above the intrusion is detected when
a user tries to log in, since the hash value of the users
password will not match. In order to detect intrusion
earlier the method can preferably comprise the further
step of comparing for each active user having access to
30 sensitive data, the hash value of the current login
password with the currently stored password hash value,
whereby said step is performed after every change of the
database content by said user.

In one embodiment, the trigger comprises means for
35 reading a log of actions on said database, means for
identifying commands for altering of user passwords in
said log and means for identifying which user passwords

Also according to the invention a impersonation prevention system for a relational database preventing an administrator impersonating another user, which database at least comprises a table with at least a user password, wherein said password is stored as a hash value, said system comprises:

trigger means, which trigger at least said calculation means for calculation of a new hash value of said password when an administrator alters said table through the database management system (DBMS) of said database; and

Such a system will overcome the risk for a DBA impersonating a user with all the advantages as the method previously described.

For exemplifying purposes, the invention will be described to embodiments thereof illustrated in the attached drawing, wherein:

Fig. 2 is a flow-chart illustrating a method according to the invention.

Referring to fig. 1, a schematic view of the components in a granular protection system of a database are shown. The central repository of the data is the database. In this case it is a relational database. An example of such a database is Oracle8®, manufactured and sold by Oracle Corporation, USA. The data is stored in

tables, which are interrelated with each other and the tables comprises columns and rows. The database can also hold other information such as information about the structure of the tables, data types of the data elements, constraints on contents in columns, user data such as password, etc. The database is operated through a database management system (DBMS). A DBMS is imposed upon the data to form a logical and structured organization of the data. A DBMS lies between the physical storage of data and the users and handles the interaction between the two.

An user normally does not operate the DBMS directly, the user uses an application which in turn operates with the DBMS. Maintenance work is performed by a database administrator (DBA), which connect direct to the DBMS. An administrator is a role with certain privileges given to a person, i.e. a special kind of user. For instance, the privileges can include allowance to add new users or read data, and normally the administrator is allowed to unrestricted use of the database. Thus, an administrator is allowed to manipulate data, manage users and other operating tasks of a database. A user, in contrast to an administrator, is normally only allowed to manipulate the actual data in the database, and often only some of the data. Which data an user can manipulate is regulated by the users permissions, which are set by the administrator.

In order to protect the data in the database an access control system (ACS) interacts with the DBMS in order to protect data from being exposed to users without the necessary rights. The access control system in the preferred embodiment could for instance be the commercially available system "Secure.Data", a system provided by the applicant. The ACS provide encryption and decryption of data, authentication of users and provides means for the security administrator (SA) to provide different users or user groups with different privileges

006277" 50052260

Thus, an user accesses the database through an application, which in turn uses the DBMS to access the database. During the access, the ACS interacts in real time with the DBMS to permit or deny the access attempt. But, a DBA will always have access to the database. However, in order to protect the information for the DBA, sensitive data is encrypted by the ACS. But, there is risk that the DBA would impersonate an user in order to gain access to decrypted data. This is as described prevented by a system and a method according to the invention. Such a system according to a preferred embodiment will now be described.

The system further comprises trigger means for triggering the calculation means for calculation of a new hash value. The trigger means survey the actions of a administrator and triggers an action when the administrator attempts to change the password of a user through the DBMS. Then the calculation means are triggered and a new hash value is calculated.

2000-01-01 10:06 1 Year 1146031000092 US U 100 10 1000.doc

implemented in the DBMS data language. The trigger could register each occasion an alter is made on the table, and preferably separate those alters that concern user passwords. Another possibility is to read the log or
 5 cache of the DBMS and search for altering statements. The trigger function could be implemented as a daemon process.

In another step, S2, depending on if a trigger has been fired, a new hash value of the same password is
 10 calculated. The new hash value differs from the previously stored hash value. This hash algorithm is not accessible by the DBA and is preferably executed within the ACS.

Then the new calculated hash value replaces the
 15 stored hash value in a step S3.

In another embodiment of the method according to the invention the integrity of the trigger is also checked at regular intervals. Otherwise, the DBA could deactivate the trigger temporarily in order to impersonate a user
 20 without being discovered. Therefore a snapshot is preferably created of the trigger. This could be done by creating a checksum or a hash value of the trigger which could be stored separately or in conjunction with the trigger.

The DBA attack will be discovered either when a user
 25 logs in or during the attempt. If the hash value of a user password is compared with the stored hash value and the comparison results in a mismatch, the user will not be able to log in. But, preferably after every action by
 30 a user, which has access to sensitive data, the hash value of the users login password should be compared with the stored password. In that way the DBA attack will be discovered sooner.

The invention has been described above in terms of a
 35 preferred embodiment. However, the scope of this invention should not be limited by this embodiment, and alternative embodiments of the invention are feasible, as

00622T" 50052260

should be appreciated by a person skilled in the art. For example, it is not necessary to use a hash algorithm for enciphering the password, instead a symmetrical or an asymmetrical encryption algorithm could be used.

- 5 Such embodiments should be considered to be within the scope of the invention, as it is defined by the appended claims.

10

09725005-112900